

eONE-FORTY 475

SILK DARK SILVER/BLACK

€ 5,190



LITE III HFS-hydroformed Prolite 66 triple butted aluminium frame featuring internal battery technology and an aggressive trail-bike geometry with 133 mm rear wheel travel. Shimano STEPS EP8 motor allows for short chain stays delivering agility. 'Smart Entry' cable routing for rattle free running. Casting motor bracket creates an integrated appearance of the motor into the frame as well as provides an extremely strong connection between chassis and motor. The frame either houses the 630 Wh battery from Shimano or the 750 Wh power pack from Simple.

CODICE PRODOTTO

M(41.5)	6110939203
L(43)	6110939214
XL(45)	6110939225
XXL(47)	6110939236

| XC/MARATHON | TRAIL | ALL MOUNTAIN | ENDURO |



FRAME	eONE-FORTY LITE III, material: aluminium, 133mm suspension travel, 27.5x2.8" max. wheelsize, 148x12mm axle standard, intube
FRAME SIZE	M, L, XL, XXL
FORK	Suntour XCR34 LOR DS, Air Boost, 140mm, Tapered, 51mm fork offset, 29x2.4" max wheelsize
SHOCK	SUNTOUR RS-EDGE-TR-LO-R8-M6, lockout
BRAKES	Shimano M4100, 4 piston, 2 piston
ROTORS	Shimano RT30 / Shimano RTEM300, 203 mm, 180 mm
HEADSET	MERIDA-8152
HANDLEBAR	MERIDA EXPERT eTR, 780mm width, 20mm rise
HANDLEBAR STEM	MERIDA EXPERT eTRII, material: aluminium, 35mm diameter, 0° stem angle, GoPro & Supernova mount, 50 mm all sizes
GRIP	MERIDA EXPERT EC
DERAILLEUR (R)	Shimano Deore RDM5120 10
SHIFTERS	Shimano SL -MT500-L clamp band / Shimano Deore M4100-RC1 clamp band 10
SEAT POST	MERIDA COMP TR, 30.9mm diameter, 0mm setback, S/M 100mm travel seatpost - L/XL 125mm travel seatpost - XXL 150mm travel seatpost
SEAT CLAMP	MERIDA EXPERT clamp
SADDLE	MERIDA COMP SL, V-mount
PEDAL	VP VPE-537

CHAIN	KMC e10s
CHAINWHEEL	Shimano CRE70-B, 34 teeth, Shimano FCME600
FREEWHEEL	Shimano M4100, 11-46 teeth, 10 speed
BOTTOM BRACKET	included
RIM	MERIDA COMP TR, 29mm inner width, material: aluminium, Tubeless ready (tubeless tape and valves not included)
HUBS	Shimano MT400-B, 110x15mm width front hub, 32 spoke holes, Centerlock, 148x12mm width rear hub, 36 spoke holes, Centerlock
AXLES	MERIDA COMP TR, including removeable lever, 6/4mm allen key
SPOKES	Black stainless
TYRES	MAXXIS REKON, 29x2.4", wire, DUAL, 27.5x2.6", wire, EXO
LIGHTS	CG-119PG-BLACK(1) / CG-404RG-BLK
FENDER	C093-02F + C093-02R
DRIVE UNIT	Shimano EP8, 85Nm
BATTERY	Simple Internal Battery, 750Wh
DISPLAY	Shimano SC-E5003A
MAX. WEIGHT	140 kg



HYDRO FORMING SYSTEM



X-TAPER HEADTUBE



SMOOTH WELDING



INTERNAL CABLE ROUTING



SMART ENTRY



D2 READY



RACELITE 61 ALUMINIUM



K-MOUNT



CASTED MOTOR BRACKET



INTERNAL BLOCK SYSTEM



ENERGY GUARD TWIST