

# eONE-SIXTY 575

MATT TITAN/BLACK

€ 5.690



**LITE III** HFS-hydroformed Prolite 66 triple butted aluminium frame featuring internal battery technology and an aggressive enduro geometry with 150 mm rear wheel travel. Shimano STEPS EP8 motor allows for short chain stays delivering agility. 'Smart Entry' cable routing for rattle free running. A casted motor bracket creates an integrated appearance of the motor into the frame as well as providing an extremely strong connection between chassis and motor. The frame either houses the 630 Wh battery from Shimano or the 750 Wh power pack from Simplo.

## CODICE PRODOTTO

**S(41,5)** 6110939009

**M(43)** 6110939010

**L(45)** 6110939021

**XL(47)** 6110939032

| XC/MARATHON | TRAIL | ALL MOUNTAIN | ENDURO |



<b>FRAME</b>	eONE-SIXTY LITE III, material: aluminium, 150mm suspension travel, 27.5x2.8" max. wheelsize, 148x12mm axle standard, intube
<b>FRAME SIZE</b>	S, M, L, XL
<b>FORK</b>	Rock Shox 35 Gold RL, Air, 160mm suspension travel, Tapered, 51mm fork offset, 29x2.8" max wheelsize
<b>SHOCK</b>	Rock Shox Deluxe Select+, platform
<b>BRAKES</b>	Shimano M4100, 4 piston
<b>ROTORS</b>	Shimano RT30 / Shimano RTEM300, 203 mm
<b>HEADSET</b>	MERIDA-8152
<b>HANDLEBAR</b>	MERIDA EXPERT eTR, 780mm width, 20mm rise
<b>HANDLEBAR STEM</b>	MERIDA EXPERT eTRII, material: aluminium, 35mm diameter, 0° stem angle, GoPro & Supernova mount, 40 mm all sizes
<b>GRIP</b>	MERIDA EXPERT EC
<b>DERAILLEUR (R)</b>	Shimano Deore RDM5100 11
<b>SHIFTERS</b>	Shimano SL -MT500-IL / Shimano Deore M5100 11
<b>SEAT POST</b>	MERIDA COMP TR, 30.9mm diameter, 0mm setback, XS/S 100mm travel seatpost - M/L 125mm travel seatpost - XL 150mm travel seatpost
<b>SEAT CLAMP</b>	MERIDA EXPERT clamp
<b>SADDLE</b>	MERIDA COMP SL, V-mount
<b>PEDAL</b>	VP VPE-537

<b>CHAIN</b>	KMC e11S EPT
<b>CHAINWHEEL</b>	Shimano CRE70B, 34 teeth, Shimano FC6M600
<b>FREEWHEEL</b>	Shimano M5100, 11-51 teeth, 11 speed
<b>BOTTOM BRACKET</b>	included
<b>RIM</b>	MERIDA COMP TR, 29mm inner width, material: aluminium, Tubeless ready (tubeless tape and valves not included)
<b>HUBS</b>	Shimano MT400-B, 110x15mm width front hub, 32 spoke holes, Centerlock, 148x12mm width rear hub, 36 spoke holes, Centerlock
<b>AXLES</b>	MERIDA EXPERT TR, including removeable lever, 6/4mm allen key
<b>SPOKES</b>	Black stainless
<b>TYRES</b>	Kenda Regolith, 29x2.4", wire, 27.5x2.6", wire
<b>LIGHTS</b>	LEZYNE E-BIKE POWER STVZO E115, reverse MERIDA Custom Mount / USB REAR Light CG-214RG
<b>FENDER</b>	C093-02F + C093-02R
<b>DRIVE UNIT</b>	Shimano EP8, 85Nm
<b>BATTERY</b>	Simplo Internal Battery, 750Wh
<b>DISPLAY</b>	Shimano SC-E5003A
<b>MAX. WEIGHT</b>	140 kg



HYDRO FORMING SYSTEM



X-TAPER HEADTUBE



SMOOTH WELDING



INTERNAL CABLE ROUTING



SMART ENTRY



D2 READY



RACELITE 61 ALUMINIUM



K-MOUNT



CASTED MOTOR BRACKET



INTERNAL BLOCK SYSTEM



ENERGY GUARD TWIST